



FERRYLL[®] SALES LIMITED

*for better rust protection and
lubrication worldwide*

CLEANING FLUID Oil and Grease Remover

Specifications

Specific Gravity at 20°C	815 kg / m ³
Flash Point	47°C ASTM D 93
Colour	Light Yellow
Supplied In	25L Drums

Application

Cleaning Fluid is an emulsifying degreasing agent, which dissolves wax, grease, oil and asphalt into a stable water based emulsion. Cleaning Fluid can be used whenever grease and oil needs to be removed, including wires, decks, shipsides, tanks, machines, machine parts, pre heaters, oil coolers, floors, brushes, etc.

Directions for Use

Decks, machines, wires, etc. should be swabbed or sprayed with Cleaning Fluid. For large amounts of grease, oil or dirt, leave for up to 30 minutes. Rinse with water.

Smaller parts, such as tools and machine parts, should be immersed for up to an hour in Cleaning Fluid and then rinsed with water.

Oil pre heaters and other systems should be circulated with Cleaning Fluid, diluted if necessary. Flush thoroughly with water.

Painted surfaces can be washed with diluted Cleaning Fluid and rinsed with water after application.

Any rinsing will be more effective with hot water.

Postal Address
One Circular Road
Douglas
Isle of Man IM1 1SB

Phone
44 (0) 1624 643643

Fax
44 (0) 1624 643802

E-mail
ferrylsalesltd@ferryl.com

Website
www.ferryl.com

Directors: H J Austin, C Bean & P J Carpenter
Registered in the Isle of Man, Company number 100504c
Registered Office: Ground Floor, One Circular Road, Douglas, Isle of Man
VAT registration # GB001 9215 25